



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Asplit® VEC Solution

**Art.-No.**

592 1020

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/mixture**

Mortar

### 1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflächenschutz Elbe GmbH	
Street:	Heuweg 4	
Place:	D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax: +49(0)3491/635-552
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de	

**1.4. Emergency telephone number:** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Regulation (EC) No. 1272/2008**

Hazard categories:  
Flammable liquid: Flam. Liq. 3  
Acute toxicity: Acute Tox. 4  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Irrit. 2  
Respiratory or skin sensitisation: Skin Sens. 1A  
Reproductive toxicity: Repr. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Specific target organ toxicity - repeated exposure: STOT RE 1  
Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:  
Flammable liquid and vapour.  
Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Suspected of damaging the unborn child.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Styrene  
Methacrylic acid  
N,N-Diethylaniline  
Cobalt bis (2-ethylhexanoate)

**Signal word:** Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 2 of 12

#### Pictograms:



#### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture containing following substances with additives

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 3 of 12

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
100-42-5	Styrene			< 40 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412			
79-41-4	Methacrylic acid			< 3 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, STOT SE 3; H332 H312 H302 H314 H335			
75-57-0	Tetramethylammonium chloride			< 1 %
	200-880-8		01-2119970924-26	
	Acute Tox. 2, Acute Tox. 3, Skin Irrit. 2, STOT SE 1, Aquatic Chronic 2; H300 H311 H315 H370 H411			
91-66-7	N,N-Diethylaniline			< 1 %
	202-088-8	612-054-00-8	01-2119943758-22	
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 2; H331 H311 H301 H373 H411			
6846-50-0	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate			< 1 %
	229-934-9		01-2119451093-47	
	Repr. 2, Aquatic Chronic 3; H361d H412			
136-52-7	Cobalt bis (2-ethylhexanoate)			< 1 %
	205-250-6		01-2119524678-29	
	Repr. 1B, Eye Irrit. 2, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 3; H360Fd H319 H317 H400 H412			
123-31-9	Hydroquinone			< 0,1 %
	204-617-8	604-005-00-4	01-2119524016-51	
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1 (M-Factor = 10); H351 H341 H302 H318 H317 H400			

Full text of H and EUH statements: see section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

###### After inhalation

- Move to fresh air in case of accidental inhalation of vapours.
- Seek medical treatment immediately.

###### After contact with skin

- Wash off immediately with soap and plenty of water.
- Consult a doctor if skin irritation persists.

###### After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Remove contact lens.
- Consult (eye) doctor immediately.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 4 of 12

#### After ingestion

- Do not induce vomiting.
- Summon a doctor immediately.
- Rinse out mouth and give plenty of water to drink.
- Never give anything by mouth to an unconscious person.
- Induce vomiting only upon the advice of a physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Harmful if inhaled.
- Causes skin irritation.
- May cause an allergic skin reaction.
- Causes serious eye irritation.
- May cause respiratory irritation.
- Causes damage to organs through prolonged or repeated exposure. (the ear)
- Suspected of damaging the unborn child.
- Attention. Beware, danger of aspiration.

#### 4.3. Indication of any immediate medical attention and special treatment needed

- Treat symptoms.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

- Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### Unsuitable extinguishing media

- Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

- Fire may produce:
  - carbon monoxide and carbon dioxide
  - Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

#### 5.3. Advice for firefighters

- Wear self-contained breathing apparatus and protective suit.

#### Additional information

- Vapours are heavier than air and spread along ground.
- The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
- Cool containers at risk with water spray jet.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- In case of vapour formation use respirator.
- Ensure adequate ventilation.
- Remove persons to safety.
- Use personal protective clothing.
- Keep away sources of ignition.

#### 6.2. Environmental precautions

- Do not discharge into the drains/surface waters/ground water.

#### 6.3. Methods and material for containment and cleaning up

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.

#### 6.4. Reference to other sections

- Observe protective instructions (see Sections 7 and 8).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® VEC Solution**

Revision date: 07.08.2019

Product code: 00359-1215

Page 5 of 12

Information for disposal see section 13.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- Keep container tightly closed.
- Vapours are heavier than air and spread along ground.
- Use only in thoroughly ventilated areas.
- Provide suitable extraction at the processing machines.

**Advice on protection against fire and explosion**

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.
- Avoid temperatures above 50°C.

**Hints on joint storage**

- Incompatible with:  
Oxidizing agents, Metal halogenides, Peroxides

**Further information on storage conditions**

- Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Mortar

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-31-9	Hydroquinone	-	0.5		TWA (8 h)	WEL
79-41-4	Methacrylic acid	20	72		TWA (8 h)	WEL
		40	143		STEL (15 min)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

- Ensure adequate ventilation, especially in confined areas.
- Pay attention to explosion protection guidelines.

**Protective and hygiene measures**

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.
- Remove and wash contaminated clothes before re-use.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 6 of 12

#### Eyeface protection

Tightly fitting goggles (EN 166).  
Eye wash bottle with pure water (EN 15154).

#### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

#### Skin protection

Long sleeved clothing (DIN EN ISO 6530)  
Solvent-resistant apron (EN 467).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow
Odour:	Pungent

#### Test method

pH-Value:	n.d.
-----------	------

#### Changes in the physical state

Melting point:	n.d.
Initial boiling point and boiling range:	145 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	29,4 °C

#### Flammability

Solid:	n.a.
Gas:	n.a.

#### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,0 vol. %
Upper explosion limits:	1,6 vol. %
Ignition temperature:	490 °C

#### Auto-ignition temperature

Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n.d.

#### Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	8,5 hPa
Density:	1,12 g/cm <sup>3</sup>

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® VEC Solution**

Revision date: 07.08.2019

Product code: 00359-1215

Page 7 of 12

Bulk density:	n.a.
Water solubility: (at 20 °C)	Immiscible
<b>Solubility in other solvents</b> n.d.	
Partition coefficient:	n.d.
Viscosity / dynamic:	n.d.
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time:	n.d.
Vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	n.d.
Solvent content:	< 5 %

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**Reactions with oxidizing agents.  
Reactions with peroxides.**10.4. Conditions to avoid**To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.  
Avoid temperatures above 50°C.  
If heating up polymerisation.**10.5. Incompatible materials**

Metal halogenides, oxidizing agents, Peroxides

**10.6. Hazardous decomposition products**Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).  
Carbon monoxide and carbon dioxide**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**Harmful if inhaled.  
No toxicological data available.  
Styrene  
LD50/oral/rat: 5000 mg/kg  
LD50/dermal/rat: > 2000 mg/kg  
LC50/inhalation/rat: 11,8 mg/l/4h



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 8 of 12

#### Irritation and corrosivity

- Causes skin irritation.
- Causes serious eye irritation.

#### Sensitising effects

- May cause an allergic skin reaction. (Cobalt bis (2-ethylhexanoate); Hydroquinone)

#### Carcinogenic/mutagenic/toxic effects for reproduction

- Suspected of damaging the unborn child. (Styrene; 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate)
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- Carcinogenicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

- May cause respiratory irritation. (Styrene; Methacrylic acid)

#### STOT-repeated exposure

- Causes damage to organs through prolonged or repeated exposure. (Styrene)

#### Aspiration hazard

- Based on available data, the classification criteria are not met.

#### Additional information on tests

- Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### Practical experience

#### Other observations

- Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
- Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

## SECTION 12: Ecological information

### 12.1. Toxicity

- Ecological data are not available.
- Harmful to aquatic life with long lasting effects.
- Styrene
- LC50/Pimephales promelas/96 h = 4,02 mg/kg
- EC50/Daphnia magna/48 h = 4,7 mg/kg
- EC50/Pseudokirchneriella subcapitata/72 h > 4,9 mg/kg

### 12.2. Persistence and degradability

- No data available

### 12.3. Bioaccumulative potential

- No data available

### 12.4. Mobility in soil

- No data available

### 12.5. Results of PBT and vPvB assessment

- According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

- Hazardous water pollutant.
- Product is toxic to fish and their nutrient animals.

#### Further information

- Do not flush into surface water or sanitary sewer system.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 9 of 12

#### Advice on disposal

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

#### Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	RESIN SOLUTION
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1

### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 10 of 12



Marine pollutant: No  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 30: Cobalt bis (2-ethylhexanoate)

2004/42/EC (VOC): < 5 %; < 90 g/l

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 11 of 12

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H360F <sub>d</sub>	May damage fertility. Suspected of damaging the unborn child.
H361 <sub>d</sub>	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® VEC Solution

Revision date: 07.08.2019

Product code: 00359-1215

Page 12 of 12

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*